# Castor SCRB125-XH-CM1230150-RHOX3050



ARTICLE NUMBER 4000487

The SCRB-XH hygienic levelling swivel castor is the optimal choice for machinery and equipment in diverse sanitary production environments.The SCRB-XH is equipped with a brake on swivel and wheel. The thread on the spindle is covered with a hygienic sleeve, which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as counter nut. Spindle parts are 100% hygienically sealed with blue sealings detectable by scanning systems.

## Technical specifications

| | | |
|---|---|---|
| Antislip | No | |
| Castor diameter | 125 mm | 4.92" |
| Drawing no. | NGI 168227 | |
| Footplate diameter | 125 mm | 4.92" |
| Height adjustment | 33 mm | 1.30" |
| Height max. | 264 mm | 10.39" |
| Height min. | 231 mm | 9.09" |
| Height total | 305 mm | 12.01" |
| Nom. load | 1500 N | |
| Nom. pull | 0 N | |
| Sleeve diameter | 30 mm | 1.18" |
| Sleeve Length | 50 mm | 1.97" |
| Spindle length | 150 mm | 5.91" |
| Thread diameter | 30 mm | 1.18" |
| Thread length | 88 mm | 3.46" |
| Thread size | M30 | |
| Thread standard | Metric C | |

## Technical specifications

