# Castor SCRB080-XH-CM12585-RHOX5820



ARTICLE NUMBER 6000536

The SCRB-XH hygienic levelling swivel castor is the optimal choice for machinery and equipment in diverse sanitary production environments.The SCRB-XH is equipped with a brake on swivel and wheel. The thread on the spindle is covered with a hygienic sleeve, which cannot be overadjusted and secures safety against exposed thread. The sleeve also functions as counter nut. Spindle parts are 100% hygienically sealed with blue sealings detectable by scanning systems.

## Technical specifications

| | | |
|---|---|---|
| Antislip | No | |
| Castor diameter | 80 mm | 3.15" |
| Drawing no. | NGI 244738 | |
| Footplate diameter | 80 mm | 3.15" |
| Height adjustment | 36 mm | 1.42" |
| Height max. | 222 mm | 8.74" |
| Height min. | 186 mm | 7.32" |
| Height total | 260 mm | 10.24" |
| Nom. load | 1500 N | |
| Sleeve diameter | 58 mm | 2.28" |
| Sleeve Length | 20 mm | 0.79" |
| Spindle length | 6 mm | 0.24" |
| Thread diameter | 58 mm | 2.28" |
| Thread length | 85 mm | 3.35" |
| Thread size | UNC 5/8 | |
| Thread standard | UNC | |

## Technical specifications

