Castor XSCB-XHC100, Blue, UNC 1 x 6,10/3,35-UNC 1 x 2,17, AISI 304



ARTICLE NUMBER 1020060

The design and patent protected XSCB-XHC certified hygienic swivel castor with a levelling spindle is the optimal choice for machinery and equipment that has to comply with strict hygiene requirements.

The XSCB-XHC is equipped with a brake on swivel and wheel which is completely integrated in the single-sided fork housing providing accessible surfaces and extreme easy access for cleaning.

The thread on the spindle is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread.

Spindle parts are 100% hygienically sealed with blue sealings detectable by scanning systems.

Technical specifications

Thread size	UNC 1	
Thread standard	UNC	
Swivel castor	Swivel	
Castor brake	Totalbrake	
Drawing no.	NGI 265947	
Castor fitting		
ElectricallyConductive		
Temperatur min	0 C	
Temperatur max	0 C	
Net weight	2577 g	
Total adjustment	36 mm	1.42”
Max. adjustment	260 mm	10.24”
Min. adjustment	224 mm	8.82”
Outer diameter	0	0.00”
Height total	298 mm	11.73”
Thread length	85 mm	3.35”
Castor diameter	100 mm	3.94”
Castor height	143 mm	5.63”
Dynamic load	1964 N	441.52lbs

Technical specifications

