Castor XSCB-XHC100, Blue, UNC 1 x 8,46/4,23-UNC 1 x 3,35, AISI 304



ARTICLE NUMBER 1020062

The design and patent protected XSCB-XHC certified hygienic swivel castor with a levelling spindle is the optimal choice for machinery and equipment that has to comply with strict hygiene requirements.

The XSCB-XHC is equipped with a brake on swivel and wheel which is completely integrated in the single-sided fork housing providing accessible surfaces and extreme easy access for cleaning.

The thread on the spindle is covered with a hygienic sleeve which cannot be overadjusted and secures safety against exposed thread.

Spindle parts are 100% hygienically sealed with blue sealings detectable by scanning systems.

Technical specifications

Thread size	UNC 1	
Thread standard	UNC	
Swivel castor	Swivel	
Castor brake	Totalbrake	
Drawing no.	NGI 265958	
Castor fitting		
ElectricallyConductive		
Temperatur min	0 C	
Temperatur max	0 C	
Net weight	2896 g	
Total adjustment	66 mm	2.60”
Max. adjustment	320 mm	12.60”
Min. adjustment	254 mm	10.00”
Outer diameter	0	0.00”
Height total	358 mm	14.09”
Thread length	115 mm	4.53”
Castor diameter	100 mm	3.94”
Castor height	143 mm	5.63”
Dynamic load	1964 N	441.52lbs

Technical specifications

