Machine foot



ARTICLE NUMBER 3001129

The design and patent protected XHJW weighing levelling foot is the optimal choice for supporting and weighing machinery, equipment, tanks and vessels in environments with strict hygienic requirements. The load cell is secured, guided and protected inside the foot.

- Secured: Load cell is secured against hazardous mechanical external impacts
- Guided: Can obtain strong forces in all directions without affecting the load cell
- Protected: Against external influences like corrosion, temperatures and bacteria

The XHJW is designed to be fastened to the floor by the two fixing holes in the footplate.

- Maintenance free and height-adjustable compact design
- Simple and fast installation - no mounting kit needed
- The different load cells cover a span of 30 kg to 5.000 kg
- Designed according to the 3-A and EHEDG hygienic standards
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 183992	
Footplate diameter	150 mm	5.91"
Height adjustment	36 mm	1.42"
Height max.	157 mm	6.18"
Height min.	121 mm	4.76"
Height total	195 mm	7.68"
Mounting holes	2 Pieces	
Nom. load	100000 N	
Nom. pull	30000 N	
Rubber type	SEPDM75	
Sleeve diameter	54 mm	2.13"
Sleeve length	50 mm	1.97"
Spindle length	150 mm	5.91"
Thread diameter	54 mm	2.13"
Thread length	88 mm	3.46"
Thread size	UNC 1 1/4-7	
Thread standard	UNC	

Technical specifications

