Machine foot HXJC-FE300(I)-HXE80250



ARTICLE NUMBER 2000199

Type HXJE + HXJCFE

The design and patent protected seismic HXJE + HXJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	No	
Drawing no.	NGI 155915	
Footplate diameter	300 mm	11.81"
Footplate shape	Drop	
Height adjustment	82 mm	3.23"
Height max.	316 mm	12.44"
Height min.	234 mm	9.21"
Height total	380 mm	14.96"
Mounting holes	4 Pieces	
Nom. Load	432000 N	
Nom. pull	39000 N	
Sleeve diameter	80 mm	3.15"
Sleeve length	55 mm	2.17"
Spindle length	255 mm	10.04"
Thread diameter	80 mm	3.15"
Thread length	210 mm	8.27"
Thread size	M80x6.00	
Thread standard	Metric C	

Technical specifications

