# Machine foot XHJC-FE300(I)-XHJ-SE72250-RH0XS7285



ARTICLE NUMBER 2000526

## Type XHJSE + XHJCFE

The design and patent protected seismic XHJSE + XHJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes and also has to to comply with the strictest hygienic requirements.

- Total seismic stability and bolted fixation to concrete floors
- Movable set-up - no concrete moulding required
- Seismic anchors chosen and approved by our experienced partner Hilti
- Patented locking mechanism secures seismic stability
- Calculated according to international seismic standard NZS 4219
- Design verified through Finite element simulation
- Designed according to the 3-A and EHEDG hygienic standards
- Certified according to USDA hygienic standard
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

| | | |
|---|---|---|
| Antislip | No | |
| Drawing no. | NGI 156273 | |
| Footplate diameter | 300 mm | 11.81" |
| Footplate shape | Drop | |
| Height adjustment | 40 mm | 1.57" |
| Height max. | 295 mm | 11.61" |
| Height min. | 255 mm | 10.04" |
| Height total | 380 mm | 14.96" |
| Mounting holes | 4 Pieces | |
| Nom. Load | 327000 N | |
| Nom. pull | 39000 N | |
| Sleeve diameter | 72 mm | 2.83" |
| Sleeve length | 85 mm | 3.35" |
| Spindle length | 255 mm | 10.04" |
| Thread diameter | 72 mm | 2.83" |
| Thread length | 164 mm | 6.46" |
| Thread size | M72x6.0 | |
| Thread standard | Metric C | |

## Technical specifications

