Machine foot HXJE150(s)-HXE56260



ARTICLE NUMBER 2000241

Type HXJE + HXJCFE

The design and patent protected seismic HXJE + HXJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact desig
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 154585	
Footplate diameter	150 mm	5.91"
Footplate shape	Round	
Height adjustment	135 mm	5.31"
Height max.	298 mm	11.73"
Height min.	163 mm	6.42"
Height total	343 mm	13.50"
Mounting holes	3 Pieces	
Nom. Load	140000 N	
Nom. pull	28000 N	
Rubber type	SEPDM75	
Sleeve diameter	56 mm	2.20"
Sleeve length	55 mm	2.17"
Spindle length	265 mm	10.43"
Thread diameter	56 mm	2.20"
Thread length	225 mm	8.86"
Thread size	M56x5.5	
Thread standard	Metric C	

Technical specifications



