Machine foot HXJE-HEX200(s)-HXEH30150



ARTICLE NUMBER 2000282

Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindl
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 154917	
Footplate diameter	199 mm	7.83"
Footplate shape	Round	
Height adjustment	116 mm	4.57"
Height max.	196 mm	7.72"
Height min.	80 mm	3.15"
Height total	235 mm	9.25"
Mounting holes	4 Pieces	
Nom. Load	60000 N	
Nom. pull	38000 N	
Rubber type	SEPDM75	
Sleeve diameter	30 mm	1.18"
Sleeve length	55 mm	2.17"
Spindle length	155 mm	6.10"
Thread diameter	30 mm	1.18"
Thread length	155 mm	6.10"
Thread size	M30	
Thread standard	Metric C	

Technical specifications

