# Machine foot HXJE-HEX250(I)-HXEH64200



ARTICLE NUMBER 2000324

## Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindl
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 155015 | |
| Footplate diameter | 249 mm | 9.80" |
| Footplate shape | Round | |
| Height adjustment | 122 mm | 4.80" |
| Height max. | 243 mm | 9.57" |
| Height min. | 121 mm | 4.76" |
| Height total | 326 mm | 12.83" |
| Mounting holes | 3 Pieces | |
| Nom. Load | 236000 N | |
| Nom. pull | 63000 N | |
| Rubber type | SEPDM75 | |
| Sleeve diameter | 64 mm | 2.52" |
| Sleeve length | 55 mm | 2.17" |
| Spindle length | 205 mm | 8.07" |
| Thread diameter | 64 mm | 2.52" |
| Thread length | 205 mm | 8.07" |
| Thread size | M64x6.0 | |
| Thread standard | Metric C | |

## Technical specifications

