Machine foot HXJE-HEX250(I)-HXEH72250



ARTICLE NUMBER 2000326

Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindl
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 155019	
Footplate diameter	249 mm	9.80"
Footplate shape	Round	
Height adjustment	165 mm	6.50"
Height max.	297 mm	11.69"
Height min.	132 mm	5.20"
Height total	387 mm	15.24"
Mounting holes	3 Pieces	
Nom. Load	327000 N	
Nom. pull	63000 N	
Rubber type	SEPDM75	
Sleeve diameter	72 mm	2.83"
Sleeve length	55 mm	2.17"
Spindle length	255 mm	10.04"
Thread diameter	72 mm	2.83"
Thread length	255 mm	10.04"
Thread size	M72x6.0	
Thread standard	Metric C	

Technical specifications

