Machine foot HXJE250(s)-HXE30150



ARTICLE NUMBER 2000352

Type HXJE + HXJCFE

The design and patent protected seismic HXJE + HXJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact desig
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 154646	
Footplate diameter	249 mm	9.80"
Footplate shape	Round	
Height adjustment	75 mm	2.95"
Height max.	204 mm	8.03"
Height min.	129 mm	5.08"
Height total	228 mm	8.98"
Mounting holes	4 Pieces	
Nom. Load	60000 N	
Nom. pull	61000 N	
Rubber type	SEPDM75	
Sleeve diameter	30 mm	1.18"
Sleeve length	55 mm	2.17"
Spindle length	155 mm	6.10"
Thread diameter	30 mm	1.18"
Thread length	123 mm	4.84"
Thread size	M30	
Thread standard	Metric C	

Technical specifications

