Machine foot HXJE-HEX250(s)-HXEH48200



ARTICLE NUMBER 2000368

Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindl
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 154969	
Footplate diameter	249 mm	9.80”
Footplate shape	Round	
Height adjustment	143 mm	5.63”
Height max.	228 mm	8.98”
Height min.	85 mm	3.35”
Height total	290 mm	11.42”
Mounting holes	4 Pieces	
Nom. Load	140000 N	
Nom. pull	61000 N	
Rubber type	SEPDM75	
Sleeve diameter	48 mm	1.89”
Sleeve length	55 mm	2.17”
Spindle length	205 mm	8.07”
Thread diameter	48 mm	1.89”
Thread length	205 mm	8.07”
Thread size	M48x5.0	
Thread standard	Metric C	

Technical specifications

