# Machine foot HXJE300(I)-HXE56260



ARTICLE NUMBER 2000393

## Type HXJE + HXJCFE

The design and patent protected seismic HXJE + HXJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact desig
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 154748 | |
| Footplate diameter | 299 mm | 11.77" |
| Footplate shape | Round | |
| Height adjustment | 135 mm | 5.31" |
| Height max. | 334 mm | 13.15" |
| Height min. | 199 mm | 7.83" |
| Height total | 379 mm | 14.92" |
| Mounting holes | 4 Pieces | |
| Nom. Load | 188000 N | |
| Nom. pull | 82000 N | |
| Rubber type | SEPDM75 | |
| Sleeve diameter | 56 mm | 2.20" |
| Sleeve length | 55 mm | 2.17" |
| Spindle length | 265 mm | 10.43" |
| Thread diameter | 56 mm | 2.20" |
| Thread length | 225 mm | 8.86" |
| Thread size | M56x5.5 | |
| Thread standard | Metric C | |

## Technical specifications




