Machine foot HXJE300(I)-HXE72250



ARTICLE NUMBER 2000396

Type HXJE + HXJCFE

The design and patent protected seismic HXJE + HXJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact desig
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 154754	
Footplate diameter	299 mm	11.77"
Footplate shape	Round	
Height adjustment	99 mm	3.90"
Height max.	322 mm	12.68"
Height min.	223 mm	8.78"
Height total	380 mm	14.96"
Mounting holes	4 Pieces	
Nom. Load	327000 N	
Nom. pull	82000 N	
Rubber type	SEPDM75	
Sleeve diameter	72 mm	2.83"
Sleeve length	55 mm	2.17"
Spindle length	255 mm	10.04"
Thread diameter	72 mm	2.83"
Thread length	215 mm	8.46"
Thread size	M72x6.0	
Thread standard	Metric C	

Technical specifications

