Machine foot HXJE350(I)-HXE64200



ARTICLE NUMBER 2000454

Type HXJE + HXJCFE

The design and patent protected seismic HXJE + HXJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact desig
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 154788	
Footplate diameter	349 mm	13.74"
Footplate shape	Round	
Height adjustment	62 mm	2.44"
Height max.	268 mm	10.55"
Height min.	206 mm	8.11"
Height total	319 mm	12.56"
Mounting holes	6 Pieces	
Nom. Load	236000 N	
Nom. pull	90000 N	
Rubber type	SEPDM75	
Sleeve diameter	64 mm	2.52"
Sleeve length	55 mm	2.17"
Spindle length	205 mm	8.07"
Thread diameter	64 mm	2.52"
Thread length	164 mm	6.46"
Thread size	M64x6.0	
Thread standard	Metric C	

Technical specifications



