# Machine foot HXJE-HEX350(I)-HXEH72310



ARTICLE NUMBER 2000467

## Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindl
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 155120 | |
| Footplate diameter | 349 mm | 13.74" |
| Footplate shape | Round | |
| Height adjustment | 223 mm | 8.78" |
| Height max. | 355 mm | 13.98" |
| Height min. | 132 mm | 5.20" |
| Height total | 445 mm | 17.52" |
| Mounting holes | 6 Pieces | |
| Nom. Load | 327000 N | |
| Nom. pull | 90000 N | |
| Rubber type | SEPDM75 | |
| Sleeve diameter | 72 mm | 2.83" |
| Sleeve length | 55 mm | 2.17" |
| Spindle length | 313 mm | 12.32" |
| Thread diameter | 72 mm | 2.83" |
| Thread length | 313 mm | 12.32" |
| Thread size | M72x6.0 | |
| Thread standard | Metric C | |

## Technical specifications

