Machine foot HXJE150(s)-HXE5492



ARTICLE NUMBER 2000536

Type HXJE + HXJCFE

The design and patent protected seismic HXJE + HXJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact desig
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 168281	
Footplate diameter	150 mm	5.91"
Footplate shape	Round	
Height adjustment	135 mm	5.31"
Height max.	283 mm	11.14"
Height min.	129 mm	5.08"
Height total	307 mm	12.09"
Mounting holes	3 Pieces	
Nom. Load	60000 N	
Nom. pull	28000 N	
Rubber type	SEPDM75	
Sleeve diameter	30 mm	1.18"
Sleeve length	55 mm	2.17"
Spindle length	234 mm	9.21"
Thread diameter	54 mm	2.13"
Thread length	202 mm	7.95"
Thread size	UNC 1 1/4-7	
Thread standard	UNC	

Technical specifications