# Machine foot HXJE150(s)-HXE36310



ARTICLE NUMBER 2000573

## Type HXJE + HXJCFE

The design and patent protected seismic HXJE + HXJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact desig
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 214370 | |
| Footplate diameter | 150 mm | 5.91" |
| Footplate shape | Round | |
| Height adjustment | 125 mm | 4.92" |
| Height max. | 259 mm | 10.20" |
| Height min. | 134 mm | 5.28" |
| Height total | 388 mm | 15.28" |
| Mounting holes | 3 Pieces | |
| Nom. Load | 96000 N | |
| Nom. pull | 28000 N | |
| Sleeve diameter | 36 mm | 1.42" |
| Sleeve length | 55 mm | 2.17" |
| Spindle length | 315 mm | 12.40" |
| Thread diameter | 36 mm | 1.42" |
| Thread length | 283 mm | 11.14" |
| Thread size | M36 | |
| Thread standard | Metric C | |

## Technical specifications

