# Machine foot XHJ-SE250(I)-XHJ-SE90310-RHOXS90115



ARTICLE NUMBER 2000115

## Type XHJSE + XHJCFE

The design and patent protected seismic XHJSE + XHJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes and also has to to comply with the strictest hygienic requirements.

- Total seismic stability and bolted fixation to concrete floors
- Movable set-up - no concrete moulding required
- Seismic anchors chosen and approved by our experienced partner Hilti
- Patented locking mechanism secures seismic stability
- Calculated according to international seismic standard NZS 4219
- Design verified through Finite element simulation
- Designed according to the 3-A and EHEDG hygienic standards
- Certified according to USDA hygienic standard
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 146790 | |
| Footplate diameter | 249 mm | 9.80” |
| Footplate shape | Round | |
| Height adjustment | 70 mm | 2.76” |
| Height max. | 355 mm | 13.98” |
| Height min. | 285 mm | 11.22” |
| Height total | 438 mm | 17.24” |
| Mounting holes | 3 Pieces | |
| Net weight | 30874 g | |
| Nom. load | 432000 N | 97117.46lbs |
| Nom. pull | 63000 N | 14162.96lbs |
| Rubber type | SEPDM75 | |
| Sleeve diameter | 90 mm | 3.54” |
| Sleeve length | 115 mm | 4.53” |
| Spindle length | 313 mm | 12.32” |
| Thread diameter | 90 mm | 3.54” |
| Thread length | 192 mm | 7.56” |
| Thread size | M90x6.00 | |
| Thread standard | Metric C | |

## Technical specifications

