# Machine foot XHJ-SE250(s)-XHJ-SE42150-RHOXS4255



ARTICLE NUMBER 2000120

## Type XHJSE + XHJCFE

The design and patent protected seismic XHJSE + XHJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes and also has to to comply with the strictest hygienic requirements.

- Total seismic stability and bolted fixation to concrete floors
- Movable set-up - no concrete moulding required
- Seismic anchors chosen and approved by our experienced partner Hilti
- Patented locking mechanism secures seismic stability
- Calculated according to international seismic standard NZS 4219
- Design verified through Finite element simulation
- Designed according to the 3-A and EHEDG hygienic standards
- Certified according to USDA hygienic standard
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 146760 | |
| Footplate diameter | 249 mm | 9.80” |
| Footplate shape | Round | |
| Height adjustment | 36 mm | 1.42” |
| Height max. | 200 mm | 7.87” |
| Height min. | 164 mm | 6.46” |
| Height total | 233 mm | 9.17” |
| Mounting holes | 4 Pieces | |
| Nom. Load | 140000 N | |
| Nom. pull | 61000 N | |
| Rubber type | SEPDM75 | |
| Sleeve diameter | 42 mm | 1.65” |
| Sleeve length | 55 mm | 2.17” |
| Spindle length | 155 mm | 6.10” |
| Thread diameter | 42 mm | 1.65” |
| Thread length | 83 mm | 3.27” |
| Thread size | M42 | |
| Thread standard | Metric C | |

## Technical specifications

