Machine foot XHJ-SE250(s)-XHJ-SE42210-RHOXS4285



ARTICLE NUMBER 2000121

Type XHJSE + XHJCFE

The design and patent protected seismic XHJSE + XHJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes and also has to to comply with the strictest hygienic requirements.

- Total seismic stability and bolted fixation to concrete floors
- Movable set-up - no concrete moulding required
- Seismic anchors chosen and approved by our experienced partner Hilti
- Patented locking mechanism secures seismic stability
- Calculated according to international seismic standard NZS 4219
- Design verified through Finite element simulation
- Designed according to the 3-A and EHEDG hygienic standards
- Certified according to USDA hygienic standard
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 146762	
Footplate diameter	249 mm	9.80"
Footplate shape	Round	
Height adjustment	66 mm	2.60"
Height max.	261 mm	10.28"
Height min.	195 mm	7.68"
Height total	298 mm	11.73"
Mounting holes	4 Pieces	
Nom. Load	140000 N	
Nom. pull	61000 N	
Rubber type	SEPDM75	
Sleeve diameter	42 mm	1.65"
Sleeve length	85 mm	3.35"
Spindle length	220 mm	8.66"
Thread diameter	42 mm	1.65"
Thread length	117 mm	4.61"
Thread size	M42	
Thread standard	Metric C	

Technical specifications

