# Seismic foot XHJ-SE200(s)4-XHJ-SE52200-RHOXS5270



ARTICLE NUMBER 2000538

## Type XHJSE + XHJCFE

The design and patent protected seismic XHJSE + XHJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes and also has to to comply with the strictest hygienic requirements.

- Total seismic stability and bolted fixation to concrete floors
- Movable set-up - no concrete moulding required
- Seismic anchors chosen and approved by our experienced partner Hilti
- Patented locking mechanism secures seismic stability
- Calculated according to international seismic standard NZS 4219
- Design verified through Finite element simulation
- Designed according to the 3-A and EHEDG hygienic standards
- Certified according to USDA hygienic standard
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 178071 | |
| Footplate diameter | 199 mm | 7.83” |
| Footplate shape | Round | |
| Height adjustment | 35 mm | 1.38” |
| Height max. | 225 mm | 8.86” |
| Height min. | 190 mm | 7.48” |
| Height total | 283 mm | 11.14” |
| Mounting holes | 4 Pieces | |
| Net weight | 9148 g | |
| Nom. load | 391400 N | 87990.22lbs |
| Nom. pull | 5 N | 1.12lbs |
| Rubber type | SEPDM75 | |
| Sleeve diameter | 52 mm | 2.05” |
| Sleeve length | 70 mm | 2.76” |
| Spindle length | 200 mm | 7.87” |
| Thread diameter | 52 mm | 2.05” |
| Thread length | 200 mm | 7.87” |
| Thread size | M52 | |
| Thread standard | Metric C | |

## Technical specifications



Drawing
coming soon

NGI A/S Virkelyst 5 9400 Nørresundby Denmark +45 98 17 45 00 ngi@ngi.dk