Maskinsko XHJ-SE200(s)-XHJSE36150-RHOXS3655-TIRX11436



ARTICLE NUMBER 2000597

Type XHJSE + XHJCFE

The design and patent protected seismic XHJSE + XHJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes and also has to to comply with the strictest hygienic requirements.

- Total seismic stability and bolted fixation to concrete floors
- Movable set-up - no concrete moulding required
- Seismic anchors chosen and approved by our experienced partner Hilti
- Patented locking mechanism secures seismic stability
- Calculated according to international seismic standard NZS 4219
- Design verified through Finite element simulation
- Designed according to the 3-A and EHEDG hygienic standards
- Certified according to USDA hygienic standard
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	Yes	
Drawing no.	NGI 264207	
Footplate diameter	199 mm	7.83”
Footplate shape	Round	
Height adjustment	36 mm	1.42”
Height max.	191 mm	7.52”
Height min.	158 mm	6.22”
Height total	221 mm	8.70”
Mounting holes	4 Pieces	
Nom. Load	96000 N	
Nom. pull	38000 N	
Sleeve diameter	36 mm	1.42”
Sleeve length	55 mm	2.17”
Spindle length	148 mm	5.83”
Thread diameter	36 mm	1.42”
Thread length	80 mm	3.15”
Thread size	M36	
Thread standard	Metric C	

Technical specifications