# Machine foot XHJ-SE350(I)-XHJ-SE64200-RHOXS6470



ARTICLE NUMBER 2000138

## Type XHJSE + XHJCFE

The design and patent protected seismic XHJSE + XHJCFE levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes and also has to to comply with the strictest hygienic requirements.

- Total seismic stability and bolted fixation to concrete floors
- Movable set-up - no concrete moulding required
- Seismic anchors chosen and approved by our experienced partner Hilti
- Patented locking mechanism secures seismic stability
- Calculated according to international seismic standard NZS 4219
- Design verified through Finite element simulation
- Designed according to the 3-A and EHEDG hygienic standards
- Certified according to USDA hygienic standard
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 146822 | |
| Footplate diameter | 349 mm | 13.74" |
| Footplate shape | Round | |
| Height adjustment | 35 mm | 1.38" |
| Height max. | 261 mm | 10.28" |
| Height min. | 226 mm | 8.90" |
| Height total | 319 mm | 12.56" |
| Mounting holes | 6 Pieces | |
| Nom. Load | 236000 N | |
| Nom. pull | 90000 N | |
| Rubber type | SEPDM75 | |
| Sleeve diameter | 64 mm | 2.52" |
| Sleeve length | 70 mm | 2.76" |
| Spindle length | 205 mm | 8.07" |
| Thread diameter | 64 mm | 2.52" |
| Thread length | 122 mm | 4.80" |
| Thread size | M64x6.0 | |
| Thread standard | Metric C | |

## Technical specifications

