Machine foot HXJ080-20-310, 2 fixations



ARTICLE NUMBER 1015355

Type HXJ/HXJ AS

The design and patent protected solid HXJ and HXJ AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

It is the most hygienic solid fully-threaded levelling foot that can be fastened to the floor by the two fixing holes in the footplate. Bolts, nuts and washers can be supplied.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXJ AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	No	
Drawing no.	NGI 165306	
Footplate diameter	80 mm	3.15"
Height adjustment	327 mm	12.87"
Height max.	337 mm	13.27"
Height min.	67 mm	2.64"
Height total	353 mm	13.90"
Mounting holes	2 Pieces	
Nom. load	16800 N	
Nom. pull	20000 N	
Spindle length	327 mm	12.87"
Thread diameter	20 mm	0.79"
Thread length	327 mm	12.87"
Thread size	M20	
Thread standard	Metric C	

Technical specifications

