Machine foot HXJ080-24-230, 2 fixations



ARTICLE NUMBER 1015360

Type HXJ/HXJ AS

The design and patent protected solid HXJ and HXJ AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

It is the most hygienic solid fully-threaded levelling foot that can be fastened to the floor by the two fixing holes in the footplate. Bolts, nuts and washers can be supplied.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXJ AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	No	
Drawing no.	NGI 165314	
Footplate diameter	80 mm	3.15"
Height adjustment	244 mm	9.61"
Height max.	251 mm	9.88"
Height min.	70 mm	2.76"
Height total	270 mm	10.63"
Mounting holes	2 Pieces	
Nom. load	62400 N	
Nom. pull	20000 N	
Spindle length	244 mm	9.61"
Thread diameter	24 mm	0.94"
Thread length	244 mm	9.61"
Thread size	M24	
Thread standard	Metric C	

Technical specifications

