# Machine foot HXJ080-24-310, 2 fixations



ARTICLE NUMBER 1015361

## Type HXJ/HXJ AS

The design and patent protected solid HXJ and HXJ AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

It is the most hygienic solid fully-threaded levelling foot that can be fastened to the floor by the two fixing holes in the footplate. Bolts, nuts and washers can be supplied.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXJ AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

## Technical specifications

| | | |
|---|---|---|
| Antislip | No | |
| Drawing no. | NGI 165316 | |
| Footplate diameter | 80 mm | 3.15" |
| Height adjustment | 327 mm | 12.87" |
| Height max. | 334 mm | 13.15" |
| Height min. | 70 mm | 2.76" |
| Height total | 353 mm | 13.90" |
| Mounting holes | 2 Pieces | |
| Nom. load | 34700 N | |
| Nom. pull | 20000 N | |
| Spindle length | 327 mm | 12.87" |
| Thread diameter | 24 mm | 0.94" |
| Thread length | 327 mm | 12.87" |
| Thread size | M24 | |
| Thread standard | Metric C | |

## Technical specifications

