Machine foot HXJ-AS080-34-8, 2 fixations



ARTICLE NUMBER 1015425

Type HXJ/HXJ AS

The design and patent protected solid HXJ and HXJ AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

It is the most hygienic solid fully-threaded levelling foot that can be fastened to the floor by the two fixing holes in the footplate. Bolts, nuts and washers can be supplied.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXJ AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	Yes	
Drawing no.	NGI 165627	
Footplate diameter	80 mm	3.15"
Height adjustment	203.20 mm	8.00"
Height max.	217 mm	8.54"
Height min.	73 mm	2.87"
Height total	234 mm	9.21"
Mounting holes	2 Pieces	
Nom. load	36000 N	
Nom. pull	20000 N	
Rubber type	S75	
Spindle length	203.20 mm	8.00"
Thread diameter	34 mm	1.34"
Thread length	203.20 mm	8.00"
Thread size	UNC 3/4	
Thread standard	UNC	

Technical specifications

