Machine foot HXJ150-UNC 3/4 x 10, AISI 304, Solid, 2 fixations



ARTICLE NUMBER 1015473

Type HXJ/HXJ AS

The design and patent protected solid HXJ and HXJ AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

It is the most hygienic solid fully-threaded levelling foot that can be fastened to the floor by the two fixing holes in the footplate. Bolts, nuts and washers can be supplied.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXJ AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	No	
Rubber type		
Thread size	UNC 3/4	
Thread standard	UNC	
Footplate diameter	150	
Drawing no.	NGI 165461	
Net weight	1965 g	
Height total	280 mm	11.02”
Thread length	254 mm	10.00”
Sleeve diameter	0	0.00”
Sleeve length	0	0.00”
Height max.	263 mm	10.35”
Height min.	66 mm	2.60”
Height adjustment	254 mm	10.00”
Spindle length	254 mm	10.00”
Nom. load	23000 N	5170.61lbs
Nom. pull	20000 N	4496.18lbs
Mounting holes	2 Pieces	

Technical specifications

