
Machine foot HXJ150-M36 x 100, AISI 304, Solid, 2 fixations



ARTICLE NUMBER 1015479

Type HXJ/HXJ AS

The design and patent protected solid HXJ and HXJ AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

It is the most hygienic solid fully-threaded levelling foot that can be fastened to the floor by the two fixing holes in the footplate. Bolts, nuts and washers can be supplied.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXJ AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	No	
Rubber type		
Thread size	M36	
Thread standard	Metric C	
Footplate diameter	150	
Drawing no.	NGI 165392	
Net weight	2211 g	
Height total	131 mm	5.16"
Thread length	107 mm	4.21"
Sleeve diameter	0	0.00"
Sleeve length	0	0.00"
Height max.	98 mm	3.86"
Height min.	73 mm	2.87"
Height adjustment	106 mm	4.17"
Spindle length	106 mm	4.17"
Nom. load	110000 N	24728.98lbs
Nom. pull	20000 N	4496.18lbs
Mounting holes	2 Pieces	

Technical specifications

