Machine foot HXJ-AS150-M24 x 310, AISI 304, Black NBR, 2 fixations



ARTICLE NUMBER 1015520

Type HXJ/HXJ AS

The design and patent protected solid HXJ and HXJ AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

It is the most hygienic solid fully-threaded levelling foot that can be fastened to the floor by the two fixing holes in the footplate. Bolts, nuts and washers can be supplied.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXJ AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	Yes	
Rubber type	Sh75A	
Thread size	M24	
Thread standard	Metric C	
Footplate diameter	150	
Drawing no.	NGI 165590	
Net weight	2597 g	
Height total	360 mm	14.17"
Thread length	329 mm	12.95"
Sleeve diameter	0	0.00"
Sleeve length	0	0.00"
Height max.	339 mm	13.35"
Height min.	75 mm	2.95"
Height adjustment	327 mm	12.87"
Spindle length	327 mm	12.87"
Nom. load	63800 N	14342.81lbs
Nom. pull	20000 N	4496.18lbs
Mounting holes	2 Pieces	

Technical specifications

