Machine foot HXJ-AS150-UNC 7/8 x 8, AISI 304, Black NBR, 2 fixations



ARTICLE NUMBER 1015551

Type HXJ/HXJ AS

The design and patent protected solid HXJ and HXJ AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

It is the most hygienic solid fully-threaded levelling foot that can be fastened to the floor by the two fixing holes in the footplate. Bolts, nuts and washers can be supplied.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXJ AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	Yes	
Rubber type	Sh75A	
Thread size	UNC 7/8	
Thread standard	UNC	
Footplate diameter	150	
Drawing no.	NGI 165679	
Net weight	2123 g	
Height total	234 mm	9.21”
Thread length	203 mm	7.99”
Sleeve diameter	0	0.00”
Sleeve length	0	0.00”
Height max.	214 mm	8.43”
Height min.	76 mm	2.99”
Height adjustment	203.20 mm	8.00”
Spindle length	203.20 mm	8.00”
Nom. load	59100 N	13286.21lbs
Nom. pull	20000 N	4496.18lbs
Mounting holes	2 Pieces	

Technical specifications

