Machine foot HXG125-16-100



ARTICLE NUMBER 1004883

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	No	
Drawing no.	NGI 058443	
Footplate diameter	125 mm	4.92”
Height adjustment	108 mm	4.25”
Height max.	121 mm	4.76”
Height min.	59 mm	2.32”
Height total	134 mm	5.28”
Mounting holes	0 Pieces	
Net weight	1272 g	
Nom. load	30800 N	6924.12lbs
Nom. load	30800 N	6924.12lbs
Nom. pull	20000 N	4496.18lbs
Spindle length	108 mm	4.25”
Thread diameter	16 mm	0.63”
Thread length	108 mm	4.25”
Thread size	M16	
Thread standard	Metric C	

Technical specifications

