Machine foot HXG125-20-70



ARTICLE NUMBER 1004894

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	No	
Drawing no.	NGI 058448	
Footplate diameter	125 mm	4.92"
Height adjustment	73 mm	2.87"
Height max.	83 mm	3.27"
Height min.	62 mm	2.44"
Height total	99 mm	3.90"
Mounting holes	0 Pieces	
Net weight	1280 g	
Nom. load	48200 N	10835.79lbs
Nom. load	48200 N	10835.79lbs
Nom. pull	20000 N	4496.18lbs
Spindle length	73 mm	2.87"
Thread diameter	20 mm	0.79"
Thread length	73 mm	2.87"
Thread size	M20	
Thread standard	Metric C	

Technical specifications

