Machine foot HXG125-34-12



ARTICLE NUMBER 1004906

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	No	
Drawing no.	NGI 058515	
Footplate diameter	125 mm	4.92"
Height adjustment	304.80 mm	12.00"
Height max.	314 mm	12.36"
Height min.	63 mm	2.48"
Height total	331 mm	13.03"
Mounting holes	0 Pieces	
Net weight	1710 g	
Nom. load	16000 N	3596.94lbs
Nom. load	16000 N	3596.94lbs
Nom. pull	20000 N	4496.18lbs
Spindle length	304.80 mm	12.00"
Thread diameter	34 mm	1.34"
Thread length	304.80 mm	12.00"
Thread size	UNC 3/4	
Thread standard	UNC	

Technical specifications

