Machine foot HXG125-36-180



ARTICLE NUMBER 1004913

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	No	
Drawing no.	NGI 058466	
Footplate diameter	125 mm	4.92”
Height adjustment	195 mm	7.68”
Height max.	188 mm	7.40”
Height min.	71 mm	2.80”
Height total	217 mm	8.54”
Mounting holes	0 Pieces	
Net weight	2490 g	
Nom. load	110000 N	24728.98lbs
Nom. load	110000 N	24728.98lbs
Nom. pull	20000 N	4496.18lbs
Spindle length	195 mm	7.68”
Thread diameter	36 mm	1.42”
Thread length	195 mm	7.68”
Thread size	M36	
Thread standard	Metric C	

Technical specifications

