# Machine foot HXG-AS125-M24 x 310, AISI 304, Black NBR



ARTICLE NUMBER 1005005

## Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

| Technical specifications | | |
|---|---|---|
| Antislip | Yes | |
| Rubber type | SH75A | |
| Thread size | M24 | |
| Thread standard | Metric C | |
| Footplate diameter | 125 | |
| Drawing no. | NGI 058579 | |
| Net weight | 2188 g | |
| Height total | 358 mm | 14.09” |
| Thread length | 327 mm | 12.87” |
| Sleeve diameter | 0 | 0.00” |
| Sleeve length | 0 | 0.00” |
| Height max. | 339 mm | 13.35” |
| Height min. | 73 mm | 2.87” |
| Height adjustment | 266 mm | 10.47” |
| Spindle length | 327 mm | 12.87” |
| Nom. load | 34700 N | 7800.87lbs |
| Nom. pull | 20000 N | 4496.18lbs |
| Mounting holes | 0 Pieces | |

## Technical specifications

