Machine foot HXG-AS125-30-150



ARTICLE NUMBER 1005007

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 058581	
Footplate diameter	125 mm	4.92"
Height adjustment	160 mm	6.30"
Height max.	162 mm	6.38"
Height min.	73 mm	2.87"
Height total	186 mm	7.32"
Mounting holes	0 Pieces	
Net weight	1923 g	
Nom. load	110000 N	24728.98lbs
Nom. load	110000 N	24728.98lbs
Nom. pull	20000 N	4496.18lbs
Rubber type	S75	
Spindle length	160 mm	6.30"
Thread diameter	30 mm	1.18"
Thread length	160 mm	6.30"
Thread size	M30	
Thread standard	Metric C	

Technical specifications

