Machine foot HXG-AS125-36-310



ARTICLE NUMBER 1005021

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 058589	
Footplate diameter	125 mm	4.92”
Height adjustment	327 mm	12.87”
Height max.	324 mm	12.76”
Height min.	78 mm	3.07”
Height total	353 mm	13.90”
Mounting holes	0 Pieces	
Net weight	3429 g	
Nom. load	110000 N	24728.98lbs
Nom. load	110000 N	24728.98lbs
Nom. pull	20000 N	4496.18lbs
Rubber type	S75	
Spindle length	327 mm	12.87”
Thread diameter	36 mm	1.42”
Thread length	327 mm	12.87”
Thread size	M36	
Thread standard	Metric C	

Technical specifications

