Machine foot HXG-AS125-54-8



ARTICLE NUMBER 1005031

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications		
Antislip	Yes	
Drawing no.	NGI 058634	
Height adjustment	203.20 mm	8.00"
Height max.	222 mm	8.74"
Height min.	18.80 mm	0.74"
Height total	222 mm	8.74"
Net weight	2258 g	
Nom. load	110000 N	24728.98lbs
Nom. load	110000 N	24728.98lbs
Nom. pull	20000 N	4496.18lbs
Rubber type	SH60A	
Thread diameter	54 mm	2.13"
Thread length	203.20 mm	8.00"
Thread size	UNC 1 1/4	
Thread standard	UNC	

Technical specifications



