Machine foot HXG150-36-150



ARTICLE NUMBER 1014998

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	No	
Drawing no.	NGI 164498	
Footplate diameter	150 mm	5.91"
Height adjustment	160 mm	6.30"
Height max.	152 mm	5.98"
Height min.	75 mm	2.95"
Height total	181 mm	7.13"
Mounting holes	0 Pieces	
Nom. load	110000 N	
Nom. pull	20000 N	
Spindle length	160 mm	6.30"
Thread diameter	36 mm	1.42"
Thread length	160 mm	6.30"
Thread size	M36	
Thread standard	Metric C	

Technical specifications

