Machine foot HXG080-30-310



ARTICLE NUMBER 1015032

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	No	
Drawing no.	NGI 164877	
Footplate diameter	80 mm	3.15"
Height adjustment	327 mm	12.87"
Height max.	324 mm	12.76"
Height min.	70 mm	2.76"
Height total	348 mm	13.70"
Mounting holes	0 Pieces	
Nom. load	88100 N	
Nom. pull	20000 N	
Spindle length	327 mm	12.87"
Thread diameter	30 mm	1.18"
Thread length	327 mm	12.87"
Thread size	M30	
Thread standard	Metric C	

Technical specifications

