Machine foot HXG-AS080-20-310



ARTICLE NUMBER 1015074

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	Yes	
Drawing no.	NGI 165097	
Footplate diameter	80 mm	3.15"
Height adjustment	327 mm	12.87"
Height max.	342 mm	13.46"
Height min.	72 mm	2.83"
Height total	358 mm	14.09"
Mounting holes	0 Pieces	
Nom. load	16800 N	
Nom. pull	20000 N	
Rubber type	S75	
Spindle length	327 mm	12.87"
Thread diameter	20 mm	0.79"
Thread length	327 mm	12.87"
Thread size	M20	
Thread standard	Metric C	

Technical specifications

