# Machine foot HXG-AS150-16-150



ARTICLE NUMBER 1015161

## Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

## Technical specifications

| | | |
|---|---|---|
| Antislip | Yes | |
| Drawing no. | NGI 165142 | |
| Footplate diameter | 150 mm | 5.91" |
| Height adjustment | 162 mm | 6.38" |
| Height max. | 180 mm | 7.09" |
| Height min. | 69 mm | 2.72" |
| Height total | 193 mm | 7.60" |
| Mounting holes | 0 Pieces | |
| Nom. load | 28100 N | |
| Nom. pull | 20000 N | |
| Rubber type | S75 | |
| Spindle length | 162 mm | 6.38" |
| Thread diameter | 16 mm | 0.63" |
| Thread length | 162 mm | 6.38" |
| Thread size | M16 | |
| Thread standard | Metric C | |

## Technical specifications

