
Machine foot HXG-AS150-20-70



ARTICLE NUMBER 1015171

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	Yes	
Drawing no.	NGI 165150	
Footplate diameter	150 mm	5.91"
Height adjustment	73 mm	2.87"
Height max.	88 mm	3.46"
Height min.	72 mm	2.83"
Height total	104 mm	4.09"
Mounting holes	0 Pieces	
Nom. load	48200 N	
Nom. pull	20000 N	
Rubber type	S75	
Spindle length	73 mm	2.87"
Thread diameter	20 mm	0.79"
Thread length	73 mm	2.87"
Thread size	M20	
Thread standard	Metric C	

Technical specifications

