Machine foot HXG-AS150-54-12



ARTICLE NUMBER 1015199

Type HXG/HXG AS

The design and patent protected solid HXG and HXG AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The joined connection between the spindle and the footplate is designed for high load and high pull, and the low-friction washer between the spindle and footplate ensures easy adjustment under high pressure.

The HXG AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	Yes	
Drawing no.	NGI 165283	
Footplate diameter	150 mm	5.91"
Height adjustment	304.80 mm	12.00"
Height max.	303 mm	11.93"
Height min.	79 mm	3.11"
Height total	331 mm	13.03"
Mounting holes	0 Pieces	
Nom. load	110000 N	
Nom. pull	20000 N	
Rubber type	S75	
Spindle length	304.80 mm	12.00"
Thread diameter	54 mm	2.13"
Thread length	304.80 mm	12.00"
Thread size	UNC 1 1/4-7	
Thread standard	UNC	

Technical specifications

