# Machine foot HXGT080-42-150



ARTICLE NUMBER 1015232

## Type HXGT/HXGT AS

The design and patent protected solid HXGT and HXGT AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

The HXGT and HXGT AS consist of a separated footplate and spindle connected by the diametrically centered elevation on the footplate.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The HXGT AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

## Technical specifications

| | | |
|---|---|---|
| Antislip | No | |
| Drawing no. | NGI 165739 | |
| Footplate diameter | 80 mm | 3.15" |
| Height adjustment | 150 mm | 5.91" |
| Height max. | 136 mm | 5.35" |
| Height min. | 76 mm | 2.99" |
| Height total | 170 mm | 6.69" |
| Mounting holes | 0 Pieces | |
| Nom. load | 110000 N | |
| Nom. pull | 0 N | |
| Spindle length | 150 mm | 5.91" |
| Thread diameter | 42 mm | 1.65" |
| Thread length | 150 mm | 5.91" |
| Thread size | M42 | |
| Thread standard | Metric C | |

## Technical specifications

