Machine foot HXGT-AS080-10-12



ARTICLE NUMBER 1015242

Type HXGT/HXGT AS

The design and patent protected solid HXGT and HXGT AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

The HXGT and HXGT AS consist of a separated footplate and spindle connected by the diametrically centered elevation on the footplate.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The HXGT AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	Yes	
Drawing no.	NGI 165928	
Footplate diameter	80 mm	3.15"
Height adjustment	304.80 mm	12.00"
Height max.	308 mm	12.13"
Height min.	71 mm	2.80"
Height total	331 mm	13.03"
Mounting holes	0 Pieces	
Nom. load	50200 N	
Nom. pull	0 N	
Rubber type	S75	
Spindle length	304.80 mm	12.00"
Thread diameter	10 mm	0.39"
Thread length	304.80 mm	12.00"
Thread size	UNC 1-8	
Thread standard	UNC	

Technical specifications

