Machine foot HXGT-AS080-36-230



ARTICLE NUMBER 1015262

Type HXGT/HXGT AS

The design and patent protected solid HXGT and HXGT AS levelling foot is the optimal choice for heavy machinery and equipment in diverse production environments and the most hygienic solid fully-threaded levelling foot.

The HXGT and HXGT AS consist of a separated footplate and spindle connected by the diametrically centered elevation on the footplate.

Reduced cleaning effort is obtained by the hygienic-oriented design with self-draining surfaces.

The HXGT AS is supplied with vulcanized FDA-approved, anti-vibration, anti-slip rubber, which blocks out bacteria underneath the footplate and creates a hygienic seal to the floor.

Technical specifications

Antislip	Yes	
Drawing no.	NGI 165861	
Footplate diameter	80 mm	3.15"
Height adjustment	230 mm	9.06"
Height max.	226 mm	8.90"
Height min.	76 mm	2.99"
Height total	255 mm	10.04"
Mounting holes	0 Pieces	
Nom. load	110000 N	
Nom. pull	0 N	
Rubber type	S75	
Spindle length	230 mm	9.06"
Thread diameter	36 mm	1.42"
Thread length	230 mm	9.06"
Thread size	M36	
Thread standard	Metric C	

Technical specifications

